

# CHAIN PRO

HIGH PERFORMANCE SYNTHETIC CHAIN LUBRICANT + CERFLON<sup>®</sup>

## DESCRIPTION

Chain Pro has an ultra penetrative, anti-corrosive synthetic formulation reinforced with Cerflon<sup>®</sup>. Ensures complete chain protection in all conditions.

## BASIC BENEFITS

- Reduces power loss and wear throughout the drive system by providing unequalled lubrication to all moving parts.
- Adheres to the chain even at extreme speeds.
- Waterproofs and displaces moisture.
- Extends chain and sprocket life.

## PROPERTIES

- Reliable protection against rust and corrosion.
- Outstanding penetration properties.
- Temperature range: -40°C to +250°C.
- Behaves neutral against non-metallic materials such as varnish, plastic, rubber.

## APPLICATION

For all standard and with O-RING, X-RING and Z-RING chains from motorcycles, go-karts and industrial power drives. Shake well before use. Apply to the whole length of the inner chain. Adheres completely after a few minutes. Do not spray empty the valve. In general, CHAIN PRO does not need to be removed for further treatment (except painting). CHAIN-PRO can be removed without difficulty with cleaning materials.

## TYPICALS

Form:	Aerosol
Boiling point/Boiling range:	- 44°C
Flash point:	- 97°C
Ignition temperature:	200°C
Danger of explosion:	Product is not explosive.
Vapour pressure at 20°C:	2100 hPa
Density at 20°C:	0.72500 g/cm <sup>3</sup>
Miscibility with water:	Not miscible or difficult to mix.

## PACKAGING

500 ml aerosol (12 x 500 ml carton)

