

# RESTOP

## MULTIFUNCTIONAL COOLING SYSTEM TREATMENT

### DESCRIPTION

Restop is a hi-tech product designed to provide Triple-Action servicing of the engine cooling system: 1) Repairing small leaks. 2) Lubricating the water pump. 3) Keeping the system clean and protected.

### BASIC BENEFITS

- Effectively repairs small leaks in the cooling system, eliminates the risks of coolant insufficiency in the system.
- Easy to use, without disassembly of any parts.
- Improves reliability of the cooling system.
- Avoid clogging of radiator conduits and temperature sensors.



### PROPERTIES

- Compatible with all antifreezes and coolants, also with OAT coolants (Organic Acid Technology).
- Resists to high temperatures, vibrations and pressure.
- Safe for rubber hoses, gaskets or other system components.
- Prevents build-up of calcium deposits.
- Protects cooling systems against corrosion and oxidation.
- Improves the functioning of the water pump by lubricating it.

### APPLICATION

Recommended for water cooled systems of all petrol and diesel engines.  
Preventive and problem solving application.

### DIRECTIONS FOR USE

- Warm up the engine with heater control in HOT position.
- Shake bottle well and add content to the cooling system via the expansion tank or directly into the radiator.
- Top up the system with coolant if required.
- Run engine for 5 minutes to circulate and seal leaks.
- One can of 350 ml is sufficient for the cooling system of an average car. For different engines, add 350 ml per 8-10L of coolant.
- It's recommended to clean the cooling system with R-Flush Radiator cleaner and refill with new coolant before treatment with Radiator Stop Leak.

ATTENTION: Do not open the cooling system while the engine is hot.

### TYPICALS

|                            |   |
|----------------------------|---|
| Physical state:            | Fluid.  |
| Pour point:                | 0 °C.   |
| Boiling point:             | 100 °C.                                       |
| Ignition temperature:      | Water based product                           |
| Explosive characteristics: | Product does not present an explosion hazard. |
| Density:                   | 1 kg/m <sup>3</sup> at 20° C.                 |

### PACKAGING

350 ml can (12 x 350 ml carton)