

# SUPER 5.1

## HIGH PERFORMANCE PENETRATING OIL + CERFLON®

### DESCRIPTION

Super 5.1 is a strong rust loosening, lubricative and protective multifunctional product. Its advanced formulation contains the Cerflon® reinforced lubricant. Super 5.1 is a blend of different agents with excellent corrosion protection, rust removing and water-displacing properties as well as an outstanding lubricating effect thanks to the Cerflon® reinforced lubricant.

### BASIC BENEFITS

- Dissolves dirt and rust, releasing locked by the rust parts.
- Lubricates and reduces friction in moving parts.
- Eliminates squeaks.
- Seals ignition systems.
- Universal application.
- Free of silicones.

### PROPERTIES

- Makes easier disassembly and assembly operations.
- Protects against rust and corrosion.
- Excellent penetration.
- Avoids electrical dysfunction.
- Waterproofs and displaces moisture.
- Degreases water-displacing.

### APPLICATION

The outstanding and universal properties of Super 5.1 assure a wide range of professional and DIY applications. Behaves neutral against non-metallic materials such as varnish, plastic, rubber.

Spray onto surface or parts and leave to penetrate. Do not spray empty the valve. Shake well before use. SUPER 5.1 can be removed without difficulty with cleaning materials. In general, SUPER 5.1 does not need to be removed for further treatment (except painting).

### TYPICALS

Form:	Liquid
Boiling point/Boiling range:	- 44°C
Flash point:	- 97°C
Danger of explosion:	Product is not explosive.
Vapour pressure at 20°C:	8300 hPa
Density at 20°C:	0.68900 g/cm <sup>3</sup>

### PACKAGING

500 ml aerosol (12 x 500 ml carton)

