

X1 5W50

ESTER HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Ester based synthetic high performance engine oil that provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics.

PROPERTIES

- Reduced fuel consumption and CO₂ emissions.
- Helps to deliver important boost in engine power.
- High and very stable viscosity index.
- Fast cold start.
- Delivers superior thermal stability, ensuring minimal engine deposits for cleaner internals.
- Ensures engine protection from the first moment of ignition, minimizing wear and damage.
- Protects Diesel Particle Filters.



APPLICATION

Suitable for both turbocharged and normally aspirated petrol & diesel engines.

Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6450
Viscosity 40 °C, mm ² /s	109,30
Viscosity 100 °C, mm ² /s	17,80
Viscosity Index	181
Flash Point COC, °C	232
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,7
Sulphate ash, %	0,77

SPECIFICATIONS

API SN/CF
ACEA A3/B4/C3

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum