

X4 15W40

ENGINE OIL

DESCRIPTION

Up-to-date universal engine oil produced with high quality solvent refined base oils and a well- balanced choice of additives. X4 15W40 is enriched with additives matched to the application.

PROPERTIES

- Excellent detergency minimizing deposits in the hot zone of the engine.
- Very good dispersion that prevents from precipitation and sludge.
- Powerful action against wear, corrosion and foam.
- High and stable viscosity index.
- Low ash contents.



APPLICATION

This universal lubricating oil meets the requirements of gasoline and diesel engines, with or without turbo-loading, under all operating conditions and all the year round. This oil quality is also applicable in those cases, where the engine builder allows extended oil drain intervals (up to 30.000 km). This oil is very suitable for mixed fleets. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C, kg/l	0,880
Viscosity -20 °C, mPa.s	6000
Viscosity 40 °C, mm ² /s	108,00
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	138
Flash Point COC, °C	215
Pour Point, °C	-31
Total Base Number, mgKOH/g	8,7
Sulphate Ash, %	1,05

SPECIFICATIONS

ACEA A2-96, B2-98, E2-96
API CG-4/SJ

Meets the requirements of
MB 228.1
MAN 271
Volvo VDS
Mack EO-L Plus

PACKAGING

60 L drum
208 L drum