

# VALVEX

## UPPER CYLINDER PROTECTION LUBRICANT

### DESCRIPTION

Valvex Protection Fluid is a high performance upper cylinder lubricant designed to minimize Valve Seat Recession in LPG and CNG Petrol engines.

### BASIC BENEFITS

- Protects and lubricate valves and valve seats.
- Smoother engine running.
- Improved engine reliability.
- Self-mixing.

### PROPERTIES

- No harmful effects on catalytic converters or the environment.
- Doesn't influence the octane number.
- Lubricates and creates a protective barrier between the valves and valve seats.
- Avoids mechanical damage caused by micro welding on the valve seats.
- Provides long lasting trouble free engine operation.
- Consist no lead.

### APPLICATION

Specially designed for the VAP-Saver<sup>®</sup> Lubricator equipment. For all LPG and CNG equipped petrol engines. Safe to use in vehicles fitted with catalytic convertors and oxygen sensors.

### DIRECTIONS FOR USE

Adjust the dosage of the lubricant by using the adjusting screw of the VAP SAVER UNIT, while the engine is running at idle speed:

- 8 drops per minute for a 4 cylinder engine.
- 12 drops per minute for a 6 cylinder engine.
- 16 drops per minute for an 8 cylinder engine.

Afterwards, make sure the Valvex consumption reaches a minimum of:

- 0,5L per 1000 for a 4 cylinder engine.
- 0,75L per 1000 km for a 6 cylinder engine.
- 1L per 1000 km for an 8 cylinder engine.

Note: In heavy-duty conditions or for very sensitive engines: increase the dosage by 50%.



### TYPICALS

|                         |       |
|-------------------------|-------|
| Density at 15 °C, kg/l  | 0,864 |
| Viscosity 40 °C, mml/s  | 11,92 |
| Viscosity 100 °C, mml/s | 3,07  |
| Viscosity Index         | 121   |
| Flash Point COC, °C     | 154   |
| Pour Point, °C          | - 15  |

### PACKAGING

1L can  
12 x 1L carton