

IN & OUT PETROL CLEANER

PROFESSIONAL DEEP CLEANING FUEL ADDITIVE FOR DI AND IDI PETROL ENGINES

IN&OUT PETROL CLEANER is a professional product of a new generation with a double field of action in DI and IDI petrol engines. Simultaneously acts on the fuel & injection system using detergent agents providing unequalled effectiveness.

1: Actively clean the injection system using detergent agents providing unequalled effectiveness. It will clean and eliminate deposits in the entire fuel system i.e. tank and booster pump, injection pump, intake valves (IDI engines) and injector nozzles.

2: Oxidize the carbon deposits using special active oxygen-rich polar solvent components. They will effectively deep clean the combustion chambers, exhaust system, turbo charger, particle filter and the catalytic converter.



PROPERTIES

- Eliminates deposits and cleans the entire fuel & Injection system i.e. tank and booster pump, high-pressure pump and flow control, common rail and injector nozzles.
- Restores the proper functioning of the turbo compressor and keeps the variable geometry vanes clean
- Cleans & regenerates the emissions control devices (catalytic converter and particle filter).

BENEFITS

- Optimized power, improved engine response
- Fuel economy
- Smoother engine running, less noise and vibrations
- Improved reliability
- Trouble-free operation of the emissions control devices (particle filters & catalytic converters).
- Reduced toxic and particle emissions.

APPLICATION

Use for both preventive and problem-solving treatment. It's recommended to use IN & OUT PETROL CLEANER at each service interval of the car. . It can also be used as a problem solver in case of high emissions or engine malfunctions. For all types of petrol engines (DI and IDI).

DIRECTIONS FOR USE

This treatment does not require any disassembling. Add the content (1L) to the tank and ad fuel until it contains 30L to 50L. Drive the vehicle at high load and high revs (>4000 rpm) in order to heat the engine and exhaust system. For optimum results, it is recommended to clean the intake system cleaner using the Xenum INTAKE PRO spray (REF. 4151500).

TYPICALS

Form:	Liquid
Colour:	Colorless
Odour:	Characteristic
Boiling point/Boiling range:	55°C
Flash point:	<18°C
Self-igniting:	Product is not self-igniting.
Density at 20°C:	0,818g/cm3

PACKAGING

1 L can (6 x 1 L carton)