

GP 10W40

SEMI-SYNTHETIC CARBON GRAPHITE BASED MOTOR OIL

DESCRIPTION

GP 10W40 is a unique semi-synthetic SAE 10W40 engine oil containing micro colloidal Carbon Graphite. This product outperforms largely traditional motor oils because of its unique formula. The very special mix of synthetic and mineral base oils and high tech additives, combined with Micro Carbon Graphite, provides important advantages over other oils. Reduces the friction between moving engine parts that wastefully consume fuel energy. Efficiently prevents metal-to-metal contact and friction between surface asperities. Provides unsurpassed fuel efficiency and up to twice the wear protection provided by popular semi-synthetic and even synthetic motor oils.

PROPERTIES

- Important fuel savings. (-3 to -5%)
- Substantial reduction of the internal friction.
- Significant increase of power. (+2 to +5%)
- Important reduction in oil consumption. (up to -80%)
- Noticeable reduction of engine running noise.
- Improved cold start.
- Keeps the engine cleaner.

APPLICATION

Suitable for use in all 4-stroke passenger cars and light commercial vehicles, when either petrol or diesel fuelled, turbocharged or naturally aspired. Its advanced formulation makes it ideal for all modern and high performance engines but is also a perfect choice for older cars.

Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture. The unique Micro Carbon Graphite guarantees a perfect stability of the colloidal particles. This product is 100% filter-safe.

TYPICALS

Density at 15 °C, kg/l	0,873
Viscosity -25 °C, mPa.s	6700
Viscosity 40 °C, mm ² /s	93,10
Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	154
Flash Point COC, °C	216
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,6
Sulphate Ash, %	1,02

SPECIFICATIONS

API SM/CF
ACEA A3/B3/B4

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60L drum
208L drum

