

# DEBLOCK SHOCK

HIGH PERFORMANCE “HEAVY DUTY” PENETRATION OIL + CERFLON<sup>®</sup>

## DESCRIPTION

Powerful spray to free non-destructively rusted, corroded and seized parts. The shock freezing effect (< -43 °C) causes a thermo shock and microscopic cracks in the layer of rust. This allows the lubricating ingredients to penetrate instantly and deep into the seized parts. The Cerflon<sup>®</sup> particles in the product assure low friction and improve the lubricating action when loosening bolts and nuts.

## BASIC BENEFITS

- Makes easier and faster disassembly of heavily rusted parts.
- Lubricates and reduces friction and wear in moving parts.
- Waterproofs and displaces moisture.
- Universal application.
- Free of silicones.

## PROPERTIES

- Outstanding penetration.
- Released parts remain lubricated and protected from rust and corrosion.
- Avoids electrical dysfunctions.
- Dissolves dirt and rust.
- Degreases water displacing.
- Seals ignition systems.

## APPLICATION

The outstanding and universal properties of DEBLOCK SHOCK assure a wide range of professional and DIY applications. The product is applicable in industry, workshop, farming, marine, motorcycles, bicycles, and more.

Spray on at a distance of about 10cm for at least 5 seconds. Leave to operate for a few minutes. Repeat if necessary. Do not spray empty the valve. In general, DEBLOCK SHOCK does not need to be removed for further treatment (except painting). Shake well before use.

## TYPICALS

Form:	Aerosol
Boiling point/Boiling range:	- 44°C
Flash point:	- 97°C
Danger of explosion:	Product is not explosive.
Vapour pressure at 20°C:	8300 hPa
Density at 20°C:	0.59800 g/cm <sup>3</sup>
Miscibility with water:	Not miscible or difficult to mix.

## PACKAGING

500 ml aerosol (12 x 500 ml carton)

